



# Industrial QR reader with TCP/IP network module, for production lines, Ethernet, POE, RS232, USB-C HD650-ETH

SKU: HD650-ETH | EAN: 5906935201183



**Scanning method:** automatic (when the code is brought close)

**Supported interfaces:** RS232, USB-C, PoE, Ethernet

**Protection rating:** IP65, provides protection against water, dust, and dirt ingress

**Readable barcodes:** 1D and 2D barcodes, including QR and DataMatrix, reliable reading of codes on moving production lines

# Industrial QR reader with TCP/IP network module, for production lines, Ethernet, POE, RS232, USB-C HD650-ETH

Model	HD650-ETH	Material	aluminum alloy
Confirmation of scanning	light and sound signal	Resolution	1280 x 800 px
Scan angle	horizontal 46° and vertical 29°	Print contrast	≥20%
Interface	Ethernet, POE, RS232, USB type C	Power Supply	5-36 VDC
Operating current	300 mA ±5% (typical), 450 mA ±5% (maximum)	Standby current	100 mA ±5%
Protection class	IP65	Operating temperature	-20 - 50°C
Storage temperature	-40°C - 70°C	Readable 1D codes	CODABAR, CODE 11, CODE 128, CODE 32, CODE 39, CODE 93, Code-A, Composite Code, EAN-13, EAN-8, IATA 2 z 5, Interleaved 2 of 5 (ITF), Matrix 2 z 5, MSI, Pharmacode, Plessey, RSS-14, RSS-14 Limited, RSS-Expanded, Straight 2 z 5, UPC-A, UPC-E
Readable 2D codes	Datamatrix, MaxiCode, MicroPDF417, microQR, PDF417, QR	External dimensions	3.6 x 4.3 x 2.4 cm
Weight	75 g	Package dimensions	19 x 10 x 7.2 cm
Weight with packaging	1 kg	Scanning method	automatically (after approaching the code)

