OPRINT-XA200

/ Data sheet

Thermal label printer for self-adhesive labels, barcodes, office, small, 203...

GTIN: 5906935201510



Printing method: thermal

Resolution: 203 dpi

Print speed: 160 mm/s

Max print width: 104 mm

Interface: USB

OPRINT-XA200

/ Specifications





Model	OPRINT-XA200
EAN	5906935201510
Resolution	203 dpi
Printing method	Thermal
Print speed	160 mm/s
Printing width	104 mm
Paper type	continuous, labels, folded, tag paper
Maximum paper width	110±0,5 mm
Paper thickness	0,06-0,3 mm
Reliability	100 km
Sensors	transmissive and reflective
Interface	USB
Printer command languages	CPCL, ESC/POS, TSPL
Driver	MACOS, Win 10, Win 11, Win 7, Win 8, Win XP, Win2003
Supported operating systems	Android, iOS, Windows
Working voltage	AC 100-240V, 50-60Hz
Dimensions of the device	20 x 11,5 x 10,5 cm

OPRINT-XA200

Package dimensions	21 x 18,5 x 12,6 cm
Weight	0,9 kg
Weight with packaging	1,45 kg
Operating temperature	0 to 45°C
Storage temperature	-20 - 60°C
Operating humidity	10 ~ 80% non-condensing
Storage humidity	5 ~ 95% non-condensing
Printed 1D codes	Codabar, Code 128, Code 39, Code 93, EAN 13, EAN 8, Interleaved 2 z 5 (ITF), UPC-A, UPC-E
Printed 2D codes	PDF 417, QR