HD67

/ Data sheet

Wired USB laser barcode scanner, handheld, programmable prefix and suffix HD67

GTIN: 5905669434096



Scanning method: manual (button-activated)

Light source: 650-670 nm laser

Scanning speed: 100 scans per second

Interface: USB

Cable length: 200 cm

Protection rating: IP54

Additional features: programmable prefix and suffix, cash register compatible

Set includes: scanner, USB cable, user manual

HD67

/ Specifications





Model	HD67
EAN	5905669434096
Warranty	2 years
Material	ABS+PC
Light source	650-670 nm Laser
Confirmation of scanning	Audible and visual signal (buzzer, LED)
Scanning speed	100 scans per second
Reading accuracy	0.10 mm
Reading distance	25-600 mm
Cable length	200 cm
Protection class	IP54
Dimensions of the device	65 x 160 x 90 mm
Package dimensions	210 x 115 x 85 mm
Device Weight	160 g
Weight with packaging	240 g
Operating temperature	0 - 45°C
Storage temperature	-40 - 60°C

Operating humidity	5 - 95%
Readable 1D codes	CODABAR, CODE 11, CODE 128, CODE 39, CODE 93, EAN-128, EAN-13, EAN-8, Industrial 2 of 5, Interleaved 2 of 5 (ITF), Matrix 2 of 5, MSI, UPC-A, UPC-E
Scanning engine	Laser
Interface	USB
Scanning method	manually (push button)
Reader stand	No
Built-in memory	No
Codes being read	1D (line)
Docking station	No
Long Range	No
Reading codes from the LCD screen	No
USB Receiver	No