HD630

/ Data sheet

Wired USB QR and barcode scanner with LCD screen reading, handheld HDWR HD630

GTIN: 5907614664329



Scanning method: manual (button-activated)

Codes read: 1D and 2D (QR, DataMatrix, PDF417, Aztec) from labels and screens

Scanning speed: 300 scans per second

Interface: USB (wired)

Screen reading: LCD, LED/OLED, smartphone displays

Drop resistance: up to 1.8 meters

Light source: 617nm LED

Set includes: scanner, USB cable, manual

HD630

/ Specifications





Model	HD630
EAN	5907614664329
Warranty	2 years
Light source	617nm LED
Confirmation of scanning	Audible and visual signal (buzzer, LED)
Scanning speed	300 scans per second
Drop resistance	Up to 1.8 meters
Dimensions of the device	18 x 10 x 8 cm
Package dimensions	20 x 12 x 10 cm
Weight	215 g
Weight with packaging	275 g
Operating temperature	-20 to 50 C
Storage temperature	-40 to 70 C
Readable 1D codes	Interleaved 2 of 5, CODABAR, CODE 11, CODE 128, CODE 39, CODE 93, EAN-13, EAN-8, GS1 DataBar, Industrial 2 of 5, MSI, UPC-A, UPC-E
Readable 2D codes	Aztec code, Data Matrix, Micro QR, HanXin, MaxiCode, MicroPDF417, PDF417, QR Code

Scanning engine	CMOS
Codes being read	1d-2d, 1D (line), 2D (multidimensional)
Interface	USB
Scanning method	manually (push button)
Built-in memory	No
Docking station	No
Reader stand	No
Long Range	No
Reading codes from the LCD screen	Yes
USB Receiver	No