HD-S20

/ Data sheet

Stationary QR and barcode scanner, compact, automatic, screen reading HD-S20

GTIN: 5907614664312



Scanning engine: CMOS

Codes being read: 1D and 2D (QR, Data Matrix, PDF417)

Scanning method: manual (button) / automatic (proximity)

Interface: USB, Virtual COM

Scanning speed: 500 scans/s

Screen reading: yes (LCD, LED, OLED)

Cable length: 120 cm

Device dimensions: 50 x 35 x 22 mm

HD-S20

/ Specifications





Model	HD-S20
EAN	5907614664312
Warranty	2 years
Resolution	640 x 480 px
Confirmation of scanning	Audible signal (buzzer)
Scanning speed	500 scans per second
Cable length	120 cm
Drop resistance	1.5 m
Dimensions of the device	50 x 35 x 22 mm
Package dimensions	160 x 105 x 35 mm
Device Weight	95 g
Weight with packaging	130 g
Operating temperature	-20 - 60°C
Storage temperature	-40 - 70°C
Operating humidity	5 - 95%

Readable 1D codes	GS1-DataBar, CODABAR, CODE 11, CODE 128, CODE 39, CODE 93, EAN-128, EAN-13, EAN-8, Industrial 2 of 5, Interleaved 2 of 5 (ITF), Matrix 2 of 5, MSI, UPC-A, UPC-E
Readable 2D codes	Data Matrix, Micro QR, PDF417, QR Code
Scanning engine	CMOS
Interface	USB, Virtual COM
Scanning method	manually/automatically
Reader stand	No
Built-in memory	No
Codes being read	1d-2d, 1D (line), 2D (multidimensional)
Docking station	No
Long Range	No
Reading codes from the LCD screen	Yes
USB Receiver	No