

# Industrial stationary QR barcode scanner, IP65, RS232, production line HD650

SKU: HD650-RS232 | EAN: 5906935201152



**Scanning engine:** CMOS (1280 x 800 px)

**Codes being read:** 1D and 2D (QR, Data Matrix, PDF417, MaxiCode)

**Scanning method:** automatic (proximity)

**Interface:** RS232

# Industrial stationary QR barcode scanner, IP65, RS232, production line HD650

Model	HD650-RS232	Warranty	2 years
Housing Material	Aluminium	Scan Confirmation	Audible and visual signal (buzzer, LED)
Resolution	1280 x 800 px	Scanning Angle	Horizontal 46°, vertical 29°
Print Contrast	≥20%	Interface	RS232
Power Supply	5-36 VDC	Operating Current	300 mA ±5% (typical), 450 mA ±5% (max)
Standby Current	100 mA ±5%	Protection Rating	IP65
Operating Temperature	-20 - 50°C	Storage Temperature	-40 - 70°C
Device Dimensions	36 x 43 x 24 mm	Device Weight	75 g
Packaging Dimensions	190 x 100 x 72 mm	Weight with Packaging	100 g
Readable 1D Codes	UPC-A, UPC-E, EAN-8, EAN-13, Code 128, Code 39, Code 93, Code 11, Codabar, MSI Plessey, Interleaved 2 of 5, IATA 2 of 5, Matrix 2 of 5, GS1 DataBar, GS1 DataBar Expanded, Composite Code	Readable 2D Codes	QR Code, Micro QR, Data Matrix, PDF417, Micro PDF417, MaxiCode
Scanning engine	CMOS	Scanning method	automatically (after approaching the code)
Reader stand	No	Built-in memory	No
Codes being read	1D (line), 2D (multidimensional)	Docking station	No
Long Range	No	Reading codes from the LCD screen	No
USB Receiver	No		

