

Label printer with UHF RFID and feeder, direct thermal and thermal transfer, 203 DPI OPrint-DA200R

SKU: OPrint-DA200R | EAN: 5906935201930



Printing method: thermal and thermal transfer

Resolution: 203 dpi

Print speed: 203 mm/s

Maximum print width: 104 mm

Label printer with UHF RFID and feeder, direct thermal and thermal transfer, 203 DPI OPrint-DA200R

| | | | |
|---------------------------|--|--------------------------|--|
| Model | OPrint-DA200R | Printing method | Thermal, thermal transfer (RFID-enabled) |
| Resolution | 203 dpi | Print speed | 203 mm/s |
| Printing width | 104 mm | Print length | 15,000 mm |
| Processor | 500 MHZ, 32 bits, COTEXT-M7 | RFID technology | UHF EPC Class1 Gen2 / ISO18000-6C tag support |
| Memory | 16 MB Flash, 8 MB SDRAM memory | Interface | USB 2.0 (for connection to a computer) |
| Printer command languages | TSPL, ZPL, ZPL II | Maximum ribbon length | 300 m |
| Ribbon width | 30~110 mm | Maximum roll width | 20 mm ~ 118 mm |
| Roll thickness | 0.06~1.3 mm | Roll diameter | 25.4 mm (1") |
| Label roll capacity | 127 mm | Dimensions of the device | 19 x 19,8 x 28 cm |
| Net weight | 2,7 kg | Printed 1D codes | Code 11, Code 128, Code 128UCC, Code 39, Code 93, Codebar, EAN 13, EAN 8, Interleaved 2 of 5, ITF 14, MSI Plessey, PostCode, Telepen, UPC-A, UPC-E |
| Printed 2D codes | Aztec, DataMatrix, Grid Matrix, Maxicode, Micro PDF417, Micro QR, PDF 417, QR CODE | Operating temperature | 5°C - 40°C |
| Storage temperature | -40°C - 60°C | Operating humidity | 25 ~ 85% |
| Storage humidity | 10 ~ 90% | | |

