

Thermal and thermal transfer label printer with WIFI, LAN, USB and RS232 203 DPI OPrint-DB200WN

SKU: OPrint-DB200WN | EAN: 5906935203149



Printing method: thermal and thermal transfer

Resolution: 203 dpi

Print speed: 152.4 mm/s

Maximum print width: 108 mm

Thermal and thermal transfer label printer with WIFI, LAN, USB and RS232 203 DPI OPrint-DB200WN

Model	OPrint-DB200WN	Material	ABS
Printing method	Thermal, thermal transfer	Resolution	203 dpi
Print speed	152,4 mm/s	Printing width	108 mm
Print length	2794 mm	Processor	400 MHz, 32-bit, ARM9
Memory	64 MB SDRAM	Working voltage	AC 100-240V, 50-60Hz
Interface	RS232, USB 2.0, USB Host 2.0	Communications	LAN, WIFI
Printer command languages	DPL, EPL, TSPL, ZPL, ZPL II	Maximum roll width	15~112 mm (0.6"~4.4")
Roll thickness	0,055~0,254 mm	Roll diameter	25.4 mm (1")
Label roll capacity	127 mm	Label length	5~2794 mm
Dimensions of the device	28 x 20 x 18,2 cm	Package dimensions	39,5 x 26 x 24 cm
Weight	3 kg	Weight with packaging	3,4 kg
Operating temperature	5°C - 40°C	Storage temperature	-40°C - 60°C
Operating humidity	25 ~ 85%	Storage humidity	10 ~ 90%
Printed 1D codes	Code 11, Code 128, Code 128UCC, Code 39, Code 93, Codebar, EAN 13, EAN 8, Interleaved 2 of 5, ITF 14, MSI Plessey, PostCode, Telepen, UPC-A, UPC-E	Printed 2D codes	Aztec, DataMatrix, Grid Matrix, Maxicode, Micro PDF417, Micro QR, PDF 417, QR CODE
Certificates	BIS, CB, CCC, CE, FCC		

