OPRINT-DA200N

/ Data sheet

Thermal and thermal transfer label printer, desktop, LAN, 203 dpi, USB, RS232...

GTIN: 5907614664367



Printing method: thermal and thermal transfer

Resolution: 203 dpi

Print speed: up to 203 mm/s

Maximum print width: 104 mm

Communication: USB 2.0, USB Host 2.0, RS-232, LAN

Command languages: EPL, ZPL, ZPL II, DPL, TSPL

OPRINT-DA200N

/ Specifications





Model	OPRINT-DA200N
EAN	5907614664367
Material	ABS
Printing method	Thermal, thermal transfer
Resolution	203 dpi
Print speed	203 mm/s
Printing width	104 mm
Print length	25400 mm
Processor	400 MHz, 32-bit, ARM9
Memory	128 MB SDRAM
Working voltage	AC 100-240V, 2.5A, 50-60Hz
Interface	RS232, USB 2.0, USB Host 2.0
Communications	LAN
Printer command languages	DPL, EPL, TSPL, ZPL, ZPL II
Maximum roll width	20~118 mm
Roll thickness	0,06~0,254 mm
Roll diameter	25.4 mm (1")

OPRINT-DA200N

/ Specifications

Label roll capacity	127 mm
Label length	5~25400 mm
Dimensions of the device	19 x 19,8 x 28 cm
Package dimensions	39,5 x 25,5 x 24 cm
Weight	2,8 kg
Weight with packaging	3,2 kg
Operating temperature	5°C - 40°C
Storage temperature	-40°C - 60°C
Operating humidity	25 ~ 85%
Storage humidity	10 ~ 90%
Printed 1D codes	Code 11, Code 128, Code 128UCC, Code 39, Code 93, Codebar, EAN 13, EAN 8, Interleaved 2 of 5, ITF 14, MSI Plessey, PostCode, Telepen, UPC-A, UPC-E
Printed 2D codes	Aztec, DataMatrix, Grid Matrix, Maxicode, Micro PDF417, Micro QR, PDF 417, QR CODE
Certificates	BIS, CB, CCC, CE, FCC