OPRINT-IA200WN

/ Data sheet

High-volume industrial label printer with WIFI, LAN, thermal and thermal...

GTIN: 5907614665456



Type: industrial high-volume label printer

Printing method: thermal and thermal transfer

Resolution: 203 dpi

Print speed: up to 203 mm/s

Maximum print width: 104 mm

Communication: USB 2.0, USB Host 2.0, RS-232, LAN, WIFI

Ribbon length: up to 405 m

Command languages: EPL, ZPL, ZPL II, DPL, TSPL

OPRINT-IA200WN

/ Specifications





Model	OPRINT-IA200WN
EAN	5907614665456
Material	ABS, metal
Printing method	Thermal, thermal transfer
Resolution	203 dpi
Print speed	203 mm/s
Printing width	104 mm
Print length	2286 mm
Processor	400 MHz, 32-bit, ARM9
Memory	128 MB SDRAM
Working voltage	AC 200-240V, 1.5A, 50-60Hz
Interface	RS232, USB 2.0, USB Host 2.0
Communications	LAN, WIFI
Printer command languages	DPL, EPL, TSPL, ZPL, ZPL II
Maximum roll width	20~120 mm
Roll thickness	0,06~0,254 mm
Roll diameter	25.4 ~ 76.2 mm

OPRINT-IA200WN

Label roll capacity	203 mm (8")
Label length	5~2286 mm
Dimensions of the device	25,5 x 26,5 x 42,5 cm
Package dimensions	51 x 38 x 37 cm
Weight	9,65 kg
Weight with packaging	11,5 kg
Operating temperature	5°C - 40°C
Storage temperature	-40°C - 60°C
Operating humidity	25 ~ 85%
Storage humidity	10 ~ 90%
Printed 1D codes	Code 11, Code 128, Code 128UCC, Code 39, Code 93, Codebar, EAN 13, EAN 8, Interleaved 2 of 5, ITF 14, MSI Plessey, PostCode, Telepen, UPC-A, UPC-E
Printed 2D codes	Aztec, DataMatrix, Grid Matrix, Maxicode, Micro PDF417, Micro QR, PDF 417, QR CODE
Certificates	BIS, CB, CCC, CE, FCC