# TAG-MR6P-6025

/ Data sheet

RFID UHF sticker 902-928 MHz made of foam, read range 2-4.5 m Tag-MR6P-6025

GTIN: 5906935200797



**Operating frequency**: 902-928 MHz

**Material**: foam

**Read range**: up to 2.8 m on metal, up to 1.4 m off metal (handheld reader), up to 4.5 m (stationary reader)

**Chip**: NXP UCODE 8 (EPC 128 bit, TID 96 bit)

**IP rating**: IP57

**Dimensions**: 60 × 25 × 1 mm

**Packaging**: set of 30 stickers

# TAG-MR6P-6025

/ Specifications



| | |
|---|---|
| **Model** | TAG-MR6P-6025 |
| **EAN** | 5906935200797 |
| **Color** | white |
| **Material** | foam |
| **Frequency of operation** | 902-928 MHz |
| **Reading distance** | Up to 2.8m on metal, up to 1.4m outside metal (handheld reader), up to 4.5m (stationary reader) |
| **IC type** | NXP UCODE 8 |
| **Memory** | EPC 128 bits, TID 96 bits |
| **Write cycles** | 100,000 times |
| **Data storage** | up to 50 years |
| **Recommended printer** | Zebra R110Xi4/Postek TX3R/SATO CL4NX |
| **Dimensions of the device** | 60 x 25 x 1 mm |
| **Weight** | 1.5 g |
| **Operating temperature** | -20°C to +85°C |
| **Storage temperature** | -20°C to +85°C |
| **Protection class** | IP57 |

| | |
|---|---|
| **Certificates** | Approved range, Approved RoHS, Approved CE |