OPRINT-MA300B

/ Data sheet

Mobile thermal label printer, Bluetooth, battery-powered OPrint-MA300B

GTIN: 5906935201848



Printing method: thermal

Resolution: 203 dpi

Print speed: 120 mm/s

Interface: USB 2.0, Bluetooth 4.2 BLE

OPRINT-MA300B

/ Specifications





Model	OPRINT-MA300B
EAN	5906935201848
Resolution	203 dpi
Printing method	Thermal
Print speed	120 mm/s
Printing width	72 mm
Print length	50 km
Processor	400 MHz, 32-bit, ARM9
Memory	8 MB PSRAM, 16 MB Flash
Sensors	gap, cover open, paper out, paper end, overheating, top black mark
Power Supply	input: AC 100–240 V, 50–60 Hz; output: DC 5 V, 2000 mA
Battery Capacity	2500 mAh / 7.4 V, rechargeable lithium battery
Interface	Bluetooth 4.2 BLE, USB 2.0
Connection ports	USB type C
Rotation	0°, 90°, 180°, 270°
Printer command languages	JPL, CPCL, ESC/POS, TSPL, ZPL

OPRINT-MA300B

/ Specifications

Roll type	Die-cut labels, Black mark labels, Continuous paper
Maximum roll width	30-80 mm
Paper tear-off mode	tear bar, manual cutting
Dimensions of the device	105 x 62 x 118 mm
Package dimensions	20 x 15 x 7 cm
Device Weight	450 g
Operating temperature	0 - 50°C
Printed 1D codes	Codabar, Code 128, Code 39, Code 93, EAN 13, EAN 8, Interleaved 2 of 5, ITF, UPC-A, UPC-E
Printed 2D codes	DataMatrix, PDF 417, QR CODE