HD29A

/ Data sheet

HD29A automatic barcode scanner with cradle

GTIN: 5905669434010



Type of scanned codes: 1D barcodes (laser)

Scanning mode: manual (trigger button) / automatic (hands-free with cradle)

Scanning speed: 200 scans per second

Available interfaces: USB, USB Virtual COM, RS232

Programmable prefix/suffix: yes (including function keys F11, F9, F7, etc.)

Protection level: IP54

Set includes: scanner, dedicated cradle, USB cable, user manual

HD29A

/ Specifications



Model	HD29A
EAN	5905669434010
Material	ABS+PC
Light source	650nm Laser
Current consumption	85 mA
Cable length	200 cm
Protection class	IP54
Dimensions of the device	65 x 165 x 90 mm
Dimensions of stand	120 x 150 x 240 mm
Package dimensions	220 x 130 x 90 mm
Device Weight	200 g
Weight with packaging	350 g
Operating temperature	0 to 45°C
Storage temperature	-40 to 60°C
Operating humidity	5 to 90%
Storage humidity	5 to 90%

Readable 1D codes	chinese code, Full ASCII Code 39, Code 39 Trioptic, GS1 DataBar RSS , IATA, MSI/Plessey, RSS variants, UK/Plessey, UPC/EAN with add-ons, CHINESE 2 of 5, CODABAR, CODE 11, CODE 128, Code 128 Full ASCII, CODE 39, CODE 93, Discrete 2 of 5, Interleaved 2 of 5 (ITF), MSI, UCC/EAN 128, UPC/EAN
Scanning engine	Laser
Codes being read	1D (line)
Scanning method	automatically (after approaching the code), manually (push button)
Built-in memory	No
Docking station	No
Interface	RS232, USB
Long Range	No
Reader stand	Yes
Reading codes from the LCD screen	No
USB Receiver	No
Scanning speed	200 scans/second
Confirmation of scanning	light signal, sound signal