

HD29A automatic barcode scanner with cradle

SKU: HD29A | EAN: 5905669434010



Type of scanned codes: 1D barcodes (laser)

Scanning mode: manual (trigger button) / automatic (hands-free with cradle)

Scanning speed: 200 scans per second

Available interfaces: USB, USB Virtual COM, RS232

HD29A automatic barcode scanner with cradle

Model	HD29A	Material of workmanship	ABS + PC
Source of light	Laser 650nm	Power consumption	85 mA
interface	USB, RS232	Cable length	200 cm
Level of security	IP54	Device dimensions	65 x 165 x 90 mm
Stand dimensions	120 x 150 x 240 mm	Size of the package	220 x 130 x 90 mm
Device weight	200 g	Weight with packaging	350 g
Working temperature	0 à 45°C	Storage temperature	-40 à 60°C
Working humidity	5 à 90%	Storage humidity	5 à 90%
Readable 1D codes	UPC/EAN, UPC/EAN z dodatkami, UCC/EAN 128, Code 39, Code 39 Full ASCII, Code 39 trioptique, Code 128, Code 128 Full ASCII, Codabar, Entrelacé 2 z 5 (ITF), Discrete 2 z 5, Code 93, MSI, Code 11, RSS warianty, Chinese 2 z 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, chinese code, ATA, GS1 DataBar, RSS	Scanning engine	Laser
Codes being read	1D (line)	Scanning method	automatically (after approaching the code), manually (push button)
Built-in memory	No	Docking station	No
Long Range	No	Reader stand	Yes
Reading codes from the LCD screen	No	USB Receiver	No
Scanning speed	200 scans/second	Confirmation of scanning	light signal, sound signal