

OPRINT-DA200NR

/ Data sheet

Label printer with UHF RFID, LAN and feeder, direct thermal and thermal...

GTIN: 5906935204061



Printing method: thermal and thermal transfer

Resolution: 203 dpi

Print speed: 203 mm/s

Maximum print width: 104 mm

Additional features: RFID, LAN, label dispenser



Model	OPRINT-DA200NR
EAN	5906935204061
Printing method	Thermal, thermal transfer (RFID-enabled)
Resolution	203 dpi
Print speed	203 mm/s
Printing width	104 mm
Print length	15,000 mm
Processor	500 MHZ, 32 bits, COTEXT-M7
RFID technology	UHF EPC Class1 Gen2 / ISO18000-6C tag support
Memory	16 MB Flash, 8 MB SDRAM memory
Interface	USB 2.0, Ethernet (LAN, RJ45)
Printer command languages	TSPL, ZPL, ZPL II
Maximum ribbon length	300 m
Ribbon width	30~110 mm
Maximum roll width	20 mm ~ 118 mm
Roll thickness	0.06~1.3 mm
Roll diameter	25.4 mm (1")

Label roll capacity	127 mm
Dimensions of the device	19 x 19,8 x 28 cm
Net weight	2,7 kg
Printed 1D codes	Code 11, Code 128, Code 128UCC, Code 39, Code 93, Codebar, EAN 13, EAN 8, Interleaved 2 of 5, ITF 14, MSI Plessey, PostCode, Telepen, UPC-A, UPC-E
Printed 2D codes	Aztec, DataMatrix, Grid Matrix, Maxicode, Micro PDF417, Micro QR, PDF 417, QR CODE
Operating temperature	5°C - 40°C
Storage temperature	-40°C - 60°C
Operating humidity	25 ~ 85%
Storage humidity	10 ~ 90%