HD-RD20XC

/ Data sheet

RFID scanner, 13.56 MHz, Mifare-compatible, wired, USB, compact for computer...

GTIN: 5907614660840



Frequency of operation: 13,56 MHz

Reading speed: up to 200 ms

Reading method: automatically

Power supply: USB DC 5V

HD-RD20XC

/ Specifications





Model	HD-RD20XC
EAN	5907614660840
Material	ABS
Reading method	automatically
Read confirmation	Light and sound signal
Reading speed	up to 200 ms
Reading distance	0,5-80 mm
Time between readings	0,5 s
Frequency of operation	13,56 MHz
Power Supply	USB DC 5V
Interface	USB
Cable length	140 cm
Dimensions of the device	94 x 60 x 10 mm
Package dimensions	125 x 85 x 38 mm
Device Weight	130 g
Weight with packaging	300 g
Operating temperature	-10 to 70°C

Storage temperature	-20 to 80°C
Operating humidity	0 to 90%
Storage humidity	0 to 90%
Output format	10-character decimal
Readable chip types	compatible with MIFARE 1K S50, compatible with MIFARE DESFire 2K, compatible with MIFARE DESFire 4K, compatible with MIFARE DESFire 8K, compatible with MIFARE Plus S2K, compatible with MIFARE Plus S4K, compatible with MIFARE Plus X2K, compatible with MIFARE Plus X4K, compatible with MIFARE S70, NTAG213, NTAG215, NTAG216