

Stationary barcode reader and QR CMOS sensor HD-S92

SKU: HD-S92 | EAN: 5907614661106



Type: stationary barcode and QR code reader

Sensor: CMOS matrix

Scanning: manual (button) / automatic (after code approach)

Scanning speed: 2200 scans per second

Stationary barcode reader and QR CMOS sensor HD-S92

Model	HD-S92	Warranty	2 years
Light source	Red LED	Optical resolution	640 x 480 , 120 fps
Scanning method	Manual (on the button) / automatic (after approaching the code)	Confirmation of scanning	light and sound signal
Scanning speed	200 scans per second	Scanning angle	rotation: 0-360 degrees, tilt: ± 65 degrees, tilt: ± 6 5 degrees
Print contrast	min 25%	Error rate	≤ 1/2 000 000
Electrical voltage	5V DC	Operating current	390 mA (max), 220 mA (typical)
Interface	USB	Cable length	200 cm
Degree of protection	IP54	Resistance to falls	up to 1.5 m
Dimensions of the device	12 x 11 x 5,3 cm	Package dimensions	13,5 x 10,5 x 5,5 cm
Weight of the device	300 g	Weight of the device with packaging	460 g
Operating temperature	-20 to 60°C	Storage temperature	-40 to 85°C
Operating humidity	5% - 95%	Readable 1D codes	Code 39, Full ASCII Code 39, Code 32, Code 128, Code 93, Code 11, Codabar/NW7, All UPC/EAN/JAN code (EAN-13, EAN-8, UPC-A, UPC-E, EAN-128), Interleaved 2 of 5 (ITF), STD 2 z 5, Industrial 2 of 5, Matrix 2 z 5, Chinese Postage Code, IATA, MSI/PLESSY, Italian Pharmacy Code, BC-412
Readable 2D codes	QR Code, Data Matrix, PDF417, Aztec code, Maxicode	Scanning engine	CMOS
Codes being read	1D (line), 2D (multidimensional)	Reading codes from the LCD screen	Yes
Built-in memory	No	Docking station	No
Long Range	No	Reader stand	No
USB Receiver	No		

