HD-SL36A

/ Data sheet

Aztec QR code reader for registration certificates with stand, wired, screen...

GTIN: 5907614660918



Scanning: Manual (on the button) / automatic (after approaching the code)

Types of codes read: 1D and 2D barcodes, including QR and Aztec code, from paper labels and phone screens

Degree of protection: IP54

Additional features: reader stand, prefix and suffix can be programmed

HD-SL36A

/ Specifications





Model	HD-SL36A
EAN	5907614660918
Codes being read	1d-2d, 1D (line), 2D (multidimensional)
Scanning engine	CMOS
Processor	32-bit ARM
Resolution	640 x 480 px
Scanning method	automatically (after approaching the code), manually (push button)
Interface	USB, Virtual COM
Cable length	150 cm
Protection class	IP54
Dimensions of the device	16,3 x 6,8 x 8 cm
Dimensions of the base	10,7 x 8 x 13 cm
Package dimensions	10,5 x 8 x 24 cm
Device Weight	360 g
Weight with packaging	460 g
Operating temperature	-10 to 50°C

Storage temperature	- 20 - 60°C
Operating humidity	5 to 95%
Storage humidity	5 to 95%
Printed 1D codes	Codabar, Codablock F, GS1 Composite, GS1 DataBar, HongKong 2 of 5, IATA 2 of 5, Code 11, Code 128, Code 32, Code 39, Code 93, Matrix 2 of 5, microPDF, MSI Plessey, NEC 2 of 5, Pharmacode Plessey, Interleaved 2 z 5 (ITF), Straight 2 of 5, Telepen, Trioptic, UPC/EAN/JAN
Readable 2D codes	Aztec, DataMatrix (ECC 200), GoCode, HanXin, MaxiCode, microQR, QR Code
Docking station	No
Reader stand	Yes
USB Receiver	No
Built-in memory	No
Reading codes from the LCD screen	Yes
Long Range	No