

MIFARE UNIQUE 125 kHz + 13.56 MHz wired RFID card reader, USB connection to computer, mini RFID scanner HD-RD30C  
SKU: HD-RD30C | EAN: 5907614660857



**Frequency of operation:** 125 kHz, 13,56 MHz  
**Reading method:** automatically  
**Confirmation of reading:** light and sound signal  
**Power supply:** USB DC 5V

# MIFARE UNIQUE 125 kHz + 13.56 MHz wired RFID card reader, USB connection to computer, mini RFID scanner HD-RD30C

|                          |                      |                          |   |
|--------------------------|----------------------|--------------------------|---|
| Model                    | HD-RD30C             | Material                 | ABS   |
| Reading method           | automatically        | Confirmation of scanning | light and sound signal  |
| Reading speed            | up to 200 ms         | Reading distance         | 0,5-80 mm   |
| Time between readings    | 0,5 s                | Frequency of operation   | 125 kHz, 13,56 MHz  |
| Power Supply             | USB DC 5V            | Interface                | USB   |
| Dimensions of the device | 105 x 68 x 10 mm     | Package dimensions       | 125 x 85 x 38 mm  |
| Device Weight            | 140 g                | Weight with packaging    | 310 g   |
| Operating temperature    | -10 to 70°C          | Storage temperature      | -20 to 80°C   |
| Operating humidity       | 0 to 90%             | Storage humidity         | 0 to 90%  |
| Output format            | 10-character decimal | Readable chip types      | Desfiire 2K, Desfiire 4K, Desfiire 8K, EM4100, EM4200, EM4305, Mifare 1K S50, Mifare Plus S2K, Mifare Plus S4K, Mifare Plus X2K, Mifare Plus X4K, Mifare S70, NTAG213, NTAG215, NTAG216, SMC4001, T5577 |

