

Warehouse scanner, barcodes, handheld HDWR HD26C

SKU: HD26C | EAN: 5907614660369



Type of scanned codes: 1D barcodes from paper labels and phone screens

Scanning sensor: CCD matrix

Scanning mode: manual (trigger button)

Scanning speed: 100 scans per second

Warehouse scanner, barcodes, handheld HDWR HD26C

Model	HD26C	Material	ABS+PC
Light source	CCD matrix	Scanning engine	CCD
Scanning method	manually (push button)	Confirmation of scanning	LED (red and blue), Two types of sound emitted
Reading width	200 mm	Scanning speed	100 times/second
Reading accuracy	0.10-0.825 mm	Error rate	1/800 million
Wireless frequency	2,4 GHz	Interface	USB
Cable length	150 cm	Protection class	IP54
Dimensions of the device	14,5 x 5 x 7,5 cm	Dimensions of the receiver	2 x 1,5 x 0,6 cm
Package dimensions	17,5 x 9 x 6 cm	Device Weight	175 g
Weight with packaging	230 g	Operating temperature	-10 to 40°C
Storage temperature	-20 to 40°C	Operating humidity	5 to 85%
Storage humidity	5 to 85%	Readable 1D codes	EAN-8, EAN-13, UPC-A, UPC-E, CODE-128, CODE-39, CODE-93, CODE-11, GS1-DATAE, INDUS 2 of 5, IATA 2 of 5, MATRIX 2 of 5, CHINESE 2 of 5, CODABAR, MSI, other one-dimensional
Built-in memory	Yes	Reader stand	No
Reading codes from the LCD screen	Yes	Docking station	No
Codes being read	1D (line)	USB Receiver	Yes

