HD26C

/ Data sheet

Warehouse scanner, barcodes, handheld HDWR HD26C

GTIN: 5907614660369



Type of scanned codes: 1D barcodes from paper labels and phone screens

Scanning sensor: CCD matrix

Scanning mode: manual (trigger button)

Scanning speed: 100 scans per second

Wireless communication: 2.4 GHz radio (USB receiver included)

Built-in memory: up to 5000 scanned codes

Interface: USB

Protection level: IP54

HD26C

/ Specifications





Model	HD26C
EAN	5907614660369
Material	ABS+PC
Light source	CCD matrix
Scanning engine	CCD
Scanning method	manually (push button)
Confirmation of scanning	LED (red and blue), Two types of sound emitted
Reading width	200 mm
Scanning speed	100 times/second
Reading accuracy	0.10-0.825 mm
Error rate	1/800 million
Wireless frequency	2,4 GHz
Interface	USB
Cable length	150 cm
Protection class	IP54
Dimensions of the device	14,5 x 5 x 7,5 cm
Dimensions of the receiver	2 x 1,5 x 0,6 cm

Package dimensions	17,5 x 9 x 6 cm
Device Weight	175 g
Weight with packaging	230 g
Operating temperature	-10 to 40°C
Storage temperature	-20 to 40°C
Operating humidity	5 to 85%
Storage humidity	5 to 85%
Readable 1D codes	CODE-11, CODE-128, CODE-39, CODE-93, other one-dimensional, CHINESE 2 of 5, CODABAR, EAN-13, EAN-8, GS1-DATAE, IATA 2 of 5, INDUS 2 of 5, Matrix 2 of 5, MSI, UPC-A, UPC-E
Built-in memory	Yes
Reader stand	No
Reading codes from the LCD screen	Yes
Docking station	No
Codes being read	1D (line)
USB Receiver	Yes
Long Range	No