SECUREENTRY-AC100

/ Data sheet

Outdoor RFID card access control system, water resistant SecureEntry-AC100

GTIN: 5907614668778



Type of verification: RFID card 125 kHz, PIN code

Max. number of users: 1000

Max. number of RFID cards: 1000

Interface: Wiegand 26 / Wiegand 34

Reading distance: 1–6 cm

Power supply: DC 12V ± 10%, 0.1A

Housing: water-resistant ABS, suitable for outdoor use

Operating temperature: 0°C to 45°C

SECUREENTRY-AC100

/ Specifications





Model	SECUREENTRY-AC100
EAN	5907614668778
Warranty	1 year
Fabrication material	ABS
Type of device	RFID card access control system, external password
Supported RFID cards	125 kHz
Interface	Wiegand 26/ Wiegand 34
Additional features	wired doorbell control, Wiegand output, access control, switch control
Type of verification	RFID card, password
Max. number of employees in the base	1000
Max. number of RFID cards	1000
Reading distance	1-6 cm
Number of buttons	13
Button illumination	yes
Access control	yes
Voltage	DC12V±10% , Current: 0.1A

Keyboard	silicone keys
Operating temperature	0~45°C
Storage temperature	-20~ 60°C
Operating humidity	40%~90%
Storage humidity	20%~90%
Product dimensions	11 x 6 x 2,2 cm
Package dimensions	13,5 x 9,8 x 3,5 cm
Product weight	50 g
Product weight with packaging	100 g