SECUREENTRY-HL100

/ Data sheet

Electronic door handle with access control for fingerprint RFID password DC6V...

GTIN: 5907614668822



Types of verification: fingerprint, PIN code, RFID card (13.56 MHz Mifare), classic key

User capacity: 300 (fingerprints, RFID cards and PIN codes combined)

Power supply: DC6V (4× AAA alkaline batteries included) + USB external power port

Compatible door thickness: 41–55 mm

Lock insert dimensions: 35 × 85 mm

Handle direction: universal (left or right)

Anti-burglary alarm: yes (30 s alarm + 180 s keypad lockout after 5 failed attempts)

Touch keypad PIN length: 4–10 digits

SECUREENTRY-HL100

/ Specifications





Model	SECUREENTRY-HL100
EAN	5907614668822
Warranty	1 year
Device type	electronic handle with lock and access control
Supported RFID cards	13,56 MHz
Types of verification	Password, fingerprint, RFID card, key
Capacity of users in the base	300
The right door thickness	41 - 55 mm
Additional features	Touch keyboard
Mortise	35 x 85
Compatibility	Compatible with more than 10 keyways, including a European standard lock body
Handle direction	universal, left or right
Voltage	DC6V, 4 AAA alkaline batteries
Alarm voltage	4.8V
Lock size	3,8 x 29 cm
Volume level	1-6

SECUREENTRY-HL100

/ Specifications

Password length	4-10 digits
Interface	USB
Supported languages	Chinese, English
Bell/alarm	yes
Access control	yes
Package dimensions	40 x 26 x 9,2 cm
Product weight	1 kg
Weight with packaging	6 kg