SECUREENTRY-PS30-5A

/ Data sheet

Power supply for access control devices, DC12V, 5A current, metal housing...

GTIN: 5907614669034



Input voltage: AC100-240V, 50-60 Hz

Output voltage: DC12V

Output current: 5A

Electric lock delay: 0-10 s (adjustable)

Operating temperature: -20°C to 65°C

Housing: metal

Overload protection: yes (all output terminals)

Dimensions: 13 x 7.5 x 5 cm, 300 g

SECUREENTRY-PS30-5A

/ Specifications





Model	SECUREENTRY-PS30-5A
EAN	5907614669034
Warranty	1 year
Device type	power supply for access control devices
Input current	AC100-240V
Output voltage	DC12V
Output current	5A
Input frequency	50~60Hz
Output current tuning range	+/- 10% ~ +/- 15%
Charging stability	1% of typical value
Output stability	0.5% of typical value
Peak value	100mVp-p typical value
Hold time	typical value at full load is 20 ms
Operating temperature	-20°C - 65°C
Overload protection	all output terminals are short-circuit protected
Electrical interlock delay	0-10 s
Device dimensions	13 x 7,5 x 5 cm

Package dimensions	13,6 x 8,5 x 6,3 cm
Weight of the device	300 g
Weight with packaging	400 g