

Access control system, RFID card and PIN reader, Wiegand 26, 125 kHz, touch keypad, waterproof SecureEntry-AC400

SKU: SecureEntry-AC400 | EAN: 5907614669423



Verification type: RFID card 125 kHz, PIN code
Operating frequency: 125 kHz
Interface: Wiegand 26 Output
Operating voltage: DC 9V - 16V (standard 12V)

Access control system, RFID card and PIN reader, Wiegand 26, 125 kHz, touch keypad, waterproof SecureEntry-AC400

Model	SecureEntry-AC400	Warranty	1 year
Reading distance	5-10 cm	Device type	Access control reader for RFID cards
Verification type	RFID card, password	Frequency of operation	125 kHz
Type of cards read	EM	Speed of response	less than 0.2 seconds
Communication distance	100 m	Data transfer	in real time
Light signal	built-in LED (two-color LED)	Sound signal	built-in speaker (buzzer)
Audiovisual signaling	when the registered card is applied to the reader, the red LED flashes green and a beep is emitted	Keyboard and keys	touch keyboard
Resistance	protection against water ingress	Voltage	DC 9V - 16V, standard DC12
Operating current	70 mA	Access control	yes
Interface	Wiegand 26 output	Operating temperature	-25° C - 75° C
Operating humidity	10%-90%	Product dimensions	12,3 x 8,4 x 2,3 cm
Package dimensions	18,5 x 13,9 x 5,5 cm	Product weight	200 g
Product weight with packaging	400 g		

