SECUREENTRY-AC500

/ Data sheet

RFID reader for proximity card and password, access control keypad, 125 kHz...

GTIN: 5907614669454



Verification type: RFID proximity card / key fob, PIN code

Operating frequency: 125 kHz

Operating voltage: DC 12V

Interface: Wiegand 26

Max. number of users in memory: 2,000 cards and passwords

Protection rating: IP65 (water and dust resistant)

Housing material: zinc alloy, silver

SECUREENTRY-AC500

/ Specifications





Model	SECUREENTRY-AC500
EAN	5907614669454
Warranty	1 year
Fabrication material	durable zinc alloy
Color	silver
Supported RFID cards	EM
Frequency of operation	125 kHz
Device type	Access control reader for RFID card and password
Verification type	RFID card, password
Reading distance	> 10 cm
Number of buttons	13
Access control	yes
Operating voltage	DC12V
Static current	< 8mA
Interlock opening current	< 1000mA
Interface	Wiegand 26
Degree of protection	IP65

Operating temperature	-10°C - 70°C
Operating humidity	10% - 90%
Product dimensions	12 x 1,8 x 5,6 cm
Package dimensions	19,2 x 12,8 x 6,1 cm
Product weight	500 g
Product weight with packaging	700 g