

Access control reader, RFID card verification, 125 kHz, DC9-16V, compact, LED and beep, Wiegand 26/34 SecureEntry-CR60LF  
SKU: SecureEntry-CR60LF | EAN: 5907614669478



**Device type:** RFID access control reader (reader only, requires external controller)

**RFID technology:** 125 kHz (EM-compatible chips)

**Interface:** Wiegand 26 or 34 (selectable)

**Read range:** 2-10 cm (depends on card/tag)

## Access control reader, RFID card verification, 125 kHz, DC9-16V, compact, LED and beep, Wiegand 26/34 SecureEntry-CR60LF

Model	SecureEntry-CR60LF	Warranty	1 yera
Fabrication material	zinc alloy	Device type	RFID reader with acc125 kHz
Frequency of operation	125 kHz	Verification type	RFID card
Speed of response	less than 0.2 seconds	Reading distance	2-10 cm, depending on the card or tag
Access control	yes	Light signal	two-color LED
Sound signal	built-in speaker (buzzer)	Communication distance	100 meters
Data transfer	in real time	Operating voltage	DC 9V - 16V, standard 12V
Operating current	70mA	Interface	Wiegand 26 or 34
Operating temperature	-25° C - 75° C	Operating humidity	10%-90%
Product dimensions	8.6 x 8.6 x 8.2 cm	Package dimensions	10,5 x 9,6 x 3 cm
Product weight	100 g	Product weight with packaging	250 g

