

Wired laser barcode scanner with stand HD42A

SKU: HD42A | EAN: 5905669434027



Type of scanned codes: 1D barcodes

Light source: 650 nm laser

Scanning mode: manual (trigger) / automatic (hands-free with stand)

Scanning speed: 200 scans per second

Wired laser barcode scanner with stand HD42A

Model	HD42A	Warranty	2 years
Material Composition	ABS + PC	Light Source	650 nm Laser
Scanning Method	Button-activated (manual) / upon code proximity (automatic)	Scan Confirmation	Audible and visual signal
Scanning Speed	200 scans per second	Reading Width	100 mm
Reading Accuracy	0.10-0.825 mm	Interface	USB, RS232
Cable Length	200 cm	Protection Rating	IP54
Device Dimensions	65 x 135 x 90 mm	Dimensions with stand	153 x 175 x 260 mm
Packaging Dimensions	200 x 140 x 80 mm	Device Weight	115 g
Weight with Packaging	235 g	Operating Temperature	0 - 45°C
Storage Temperature	-40 - 60°C	Operating Humidity	5 - 95%
Readable 1D Codes	EAN-13, EAN-8, UPC-A, UPC-E, Code 39, Code 93, Code 128, Interleaved 2 of 5, ITF-14, Industrial 2 of 5, Matrix 2 of 5, Codabar, Code 11, GS1 DataBar, GS1 DataBar Limited, GS1 DataBar Expanded	Scanning engine	Laser
Reader stand	Yes	Built-in memory	No
Codes being read	1D (line)	Docking station	No
Long Range	No	Reading codes from the LCD screen	No
USB Receiver	No		

