HD42A

/ Data sheet

Wired laser barcode scanner with stand HD42A

GTIN: 5905669434027



Type of scanned codes: 1D barcodes

Light source: 650 nm laser

Scanning mode: manual (trigger) / automatic (hands-free with stand)

Scanning speed: 200 scans per second

Available interfaces: USB

Cable length: 200 cm

Protection level: IP54

Additional features: programmable prefix and suffix, stand included

HD42A

/ Specifications





Model	HD42A
EAN	5905669434027
Warranty	2 years
Material	ABS+PC
Light source	650 nm Laser
Confirmation of scanning	Audible and visual signal
Scanning speed	200 scans per second
Reading width	100 mm
Reading accuracy	0.10-0.825 mm
Cable length	200 cm
Protection class	IP54
Dimensions of the device	65 x 135 x 90 mm
External dimensions	153 x 175 x 260 mm
Package dimensions	200 x 140 x 80 mm
Device Weight	115 g
Weight with packaging	235 g
Operating temperature	0 - 45°C

Storage temperature	-40 - 60°C
Operating humidity	5 - 95%
Readable 1D codes	Interleaved 2 of 5, CODABAR, CODE 11, CODE 128, CODE 39, CODE 93, EAN-13, EAN-8, GS1 DataBar, GS1 DataBar Expanded, GS1 DataBar Limited, Industrial 2 of 5, ITF-14, Matrix 2 of 5, UPC-A, UPC-E
Scanning engine	Laser
Interface	RS232, USB
Scanning method	manually/automatically
Reader stand	Yes
Built-in memory	No
Codes being read	1D (line)
Docking station	No
Long Range	No
Reading codes from the LCD screen	No
USB Receiver	No