

Access control reader for RFID card and password, 125 kHz,  
Wiegand 26/34, DC 9V-16V , elegant SecureEntry-AC800LF

SKU: SecureEntry-AC800LF | EAN: 5907614669881



125 kHz

**Type of verification:** RFID card 125 kHz, PIN password

**Operating frequency:** 125 kHz

**Interface:** Wiegand 26 / 34

**Power supply:** DC 9V-16V (standard 12V), 70 mA

## Access control reader for RFID card and password, 125 kHz, Wiegand 26/34, DC 9V-16V , elegant SecureEntry-AC800LF

Model	SecureEntry-AC800LF	Warranty	1 year
Device type	Access control reader for RFID card and password	Frequency of operation	125 kHz
Verification type	RFID card, password	Speed of response	less than 0.2 seconds
Reading distance	5-10cm	Access control	yes
Light signal	two-color LED	Sound signal	built-in speaker (buzzer)
Communication distance	100 meters	Data transfer	in real time
Operating voltage	DC 9V - 16V, standard 12V	Operating current	70mA
Interface	Wiegand 26 lub 34	Operating temperature	-25° C - 75° C
Operating humidity	10%-90%	Product dimensions	8,6 x 8,6 x 2 cm
Package dimensions	10,5 x 9,5 x 2,8 cm	Product weight	100 g
Product weight with packaging	300 g		

