SECUREENTRY-AC800HF

/ Data sheet

Access control reader for 13.56 MHz RFID card and password, Wiegand 26-34, DC... GTIN: 5907614669898



Type of verification: RFID card (13.56 MHz), PIN password

Operating frequency: 13.56 MHz

Power supply: DC 9V–16V (standard 12V)

Reading range: 5–10 cm

Interface: Wiegand 26 / 34

Communication distance: up to 100 m

Operating temperature: –25°C to +75°C

SECUREENTRY-AC800HF

/ Specifications





Model	SECUREENTRY-AC800HF
EAN	5907614669898
Warranty	1 year
Device type	Access control reader for RFID card and password
Frequency of operation	13,56 MHz
Verification type	RFID card, password
Speed of response	less than 0.2 seconds
Reading distance	5-10 cm
Access control	yes
Light signal	two-color LED
Sound signal	built-in speaker (buzzer)
Communication distance	100 meters
Data transfer	in real time
Operating voltage	DC 9V – 16V, standard 12V
Operating current	70mA
Interface	Wiegand 26 lub 34
Operating temperature	-25º C – 75º C

Operating humidity	10%-90%
Product dimensions	8,6 x 8,6 x 2 cm
Package dimensions	10,5 x 9,5 x 2,8 cm
Product weight	100 g
Product weight with packaging	300 g