

Access control reader for 13.56 MHz RFID card and password,  
Wiegand 26-34, DC 9V-16V, touch keypad, compact

**SecureEntry-AC800HF**

SKU: SecureEntry-AC800HF | EAN: 5907614669898



**Type of verification:** RFID card (13.56 MHz), PIN password

**Operating frequency:** 13.56 MHz

**Power supply:** DC 9V-16V (standard 12V)

**Reading range:** 5-10 cm

# Access control reader for 13.56 MHz RFID card and password, Wiegand 26-34, DC 9V-16V, touch keypad, compact SecureEntry-AC800HF

Model	SecureEntry-AC800HF	Warranty	1 year
Device type	Access control reader for RFID card and password	Frequency of operation	13,56 MHz
Verification type	RFID card, password	Speed of response	less than 0.2 seconds
Reading distance	5-10 cm	Access control	yes
Light signal	two-color LED	Sound signal	built-in speaker (buzzer)
Communication distance	100 meters	Data transfer	in real time
Operating voltage	DC 9V - 16V, standard 12V	Operating current	70mA
Interface	Wiegand 26 lub 34	Operating temperature	-25° C - 75° C
Operating humidity	10%-90%	Product dimensions	8,6 x 8,6 x 2 cm
Package dimensions	10,5 x 9,5 x 2,8 cm	Product weight	100 g
Product weight with packaging	300 g		

