

Access control, 13.56 MHz card RFID reader, water ingress resistant, IP68, DC 9V - 16V SecureEntry-CR50HF

SKU: SecureEntry-CR50HF | EAN: 5907614669904



Verification type: RFID card 13.56 MHz
RFID standard: ISO 14443A/B (Mifare compatible)
Interface: Wiegand 26/34
Proximity range: 3-10 cm

Access control, 13.56 MHz card RFID reader, water ingress resistant, IP68, DC 9V - 16V SecureEntry-CR50HF

Model	SecureEntry-CR50HF	Warranty	1 year
Device type	RFID reader with access control	Verification type	RFID card
Fabrication material	metal	Speed of response	less than 0.2 seconds
Proximity range	3-10 cm	Communication distance	100 meters
Data transfer	in real time	Operating voltage	DC9V-16V, standard 12V
Operating current	70 mA	Light signal	Built-in LED (two-color LED)
Sound signal	Built-in speaker (buzzer)	Audiovisual signaling	when the registered card is applied to the reader, the red LED red LED flashes green and a beep is emitted
Interface	Wiegand 26/34	Supported RFID cards	13,56 MHz Mifare
Access control	yes	Degree of protection	IP68
Operating temperature	-25° C to 75° C	Operating humidity	10%-90%
Product dimensions	12 x 6,5 x 2,1 cm	Package dimensions	14,2 x 9,2 x 4,3 cm
Product weight	400 g	Product weight with packaging	500 g

