HD-S30

/ Data sheet

Stationary 1D barcode scanner, USB interface, HDWR HD-S30

GTIN: 5907614669850



Scanner type: stationary 1D barcode scanner

Scanning: automatic (on approach) or manual (button)

Readable codes: 1D barcodes from paper labels and phone screens

Interface: USB, Virtual COM

Housing: metal

Drop resistance: up to 1.2 meters

Prefix/suffix programming: yes

Plug and play: yes, no drivers required

HD-S30

/ Specifications





Model	HD-S30
EAN	5907614669850
Warranty	2 years
Light source	650nm
Cable length	150 cm
Drop resistance	up to 1.2 meters
Operating temperature	-20 to 50°C
Storage temperature	-40 to 70°C
Operating humidity	5 to 95%
Storage humidity	5 to 95%
Dimensions of the device	5.5 x 4.5 x 2 cm
Package dimensions	21.5 x 10 x 7.5 cm
Device Weight	170 g
Weight with packaging	190 g
Readable 1D codes	Code32, GS1 Composite, GS1 Data Bar, Interleaved 2 of 5, CODABAR, CODE 11, CODE 128, CODE 39, CODE 93, EAN, Febraban, IATA 2 of 5, Industrial 2 of 5, ISBN, ISSN, Matrix 2 of 5, MSI Plessey, UPC

HD-S30

Interface	USB, Virtual COM
Scanning method	automatically (after approaching the code), manually (push button)
Scanning engine	Laser
Built-in memory	No
Codes being read	1D (line)
Docking station	No
Long Range	No
Reader stand	No
Reading codes from the LCD screen	Yes
USB Receiver	No