


QR and barcode reader wired, stationary, RS232 cable HD-S63

SKU: HD-S63-RS232 | EAN: 5907614666897



Type: stationary (desktop) QR and barcode reader
Interface: RS232 (cable included)
Scanning: automatic (after code approach)
Sensor: CMOS matrix

QR and barcode reader wired, stationary, RS232 cable HD-S63

Model	HD-S63-RS232	Warranty	2 years
Matrix type	640x480 CMOS	Confirmation of scan	audible and light signals
Compatible with operating system	Linux, Android, Windows XP, 7, 8, 10, MacOS	Interface	RS232
Cable length	170 cm	Protection degree	IP54
Device dimensions	10,6 x 7,3 x 14,3 cm	Packaging dimensions	18 x 16,8 x 12,1 cm
Weight of the device	370 g	Weight of device in packaging	528 g
Operating temperature	0 do 60°C	Storage temperature	-20 do 60°C
Operating humidity	5 do 95%	Storage humidity	5 do 95%
Readable 1D codes	EAN-8, EAN-13, EAN-13, EAN-13 5, ISBN, UPC-A, UPC-E, Code 39, Code 39 FullASCII, Code 93, Code 128, Codabar, Industrial 2 of 5, Interleaved 2 of 5, Matrix 2 of 5, GS1-128, GS1 DataBar RSS14(Stacked), GS1 DataBar Limited, Standard 25, GS1 DataBar Expanded	Readable 2D codes	PDF417, MicroPDF417, MicroQR, Data Matrix, QR Code
Codes being read	1D (line), 2D (multidimensional)	Docking station	No
Reader stand	No	Reading codes from the LCD screen	Yes
Scanning engine	CMOS	USB Receiver	No
Scanning method	automatically (after approaching the code)	Built-in memory	No
Long Range	No		

