HD-S63-RS232

/ Data sheet

QR and barcode reader wired, stationary, RS232 cable HD-S63

GTIN: 5907614666897



Type: stationary (desktop) QR and barcode reader

Interface: RS232 (cable included)

Scanning: automatic (after code approach)

Sensor: CMOS matrix

Scanned codes: 1D and 2D barcodes including QR, Data Matrix, PDF417

Protection rating: IP54 (dust and splash resistant)

Compatibility: Windows XP/7/8/10, Linux, Android, macOS

HD-S63-RS232

/ Specifications





Model	HD-S63-RS232
EAN	5907614666897
Warranty	2 years
Sensors	640x480 CMOS
Confirmation of scanning	audible and light signals
Supported operating systems	Linux, Android, Windows XP, 7, 8, 10, MacOS
Cable length	170 cm
Protection class	IP54
Dimensions of the device	10,6 x 7,3 x 14,3 cm
Package dimensions	18 x 16,8 x 12,1 cm
Device Weight	370 g
Weight with packaging	528 g
Operating temperature	0 to 60°C
Storage temperature	-20 to 60°C
Operating humidity	5 to 95%
Storage humidity	5 to 95%

HD-S63-RS232

/ Specifications

Readable 1D codes	Code 39 FullASCII, EAN-13 5, GS1 DataBar RSS14 (Stacked), GS1-128, Interleaved 2 of 5, Standard 25, CODABAR, CODE 128, CODE 39, CODE 93, EAN-13, EAN-8, GS1 DataBar Expanded, GS1 DataBar Limited, Industrial 2 of 5, ISBN, Matrix 2 of 5, UPC-A, UPC-E
Readable 2D codes	Data Matrix, MicroPDF417, microQR, PDF417, QR Code
Codes being read	1d-2d, 1D (line), 2D (multidimensional)
Docking station	No
Interface	RS232
Reader stand	No
Reading codes from the LCD screen	Yes
Scanning engine	CMOS
USB Receiver	No
Scanning method	automatically (after approaching the code)
Built-in memory	No
Long Range	No