

Barcode scanner with stand, wired reader, automatic reading, RS232 interface HD10C

SKU: HD10C-RS232 | EAN: 5906935200308



Scanning speed: 200 times/second

Type of scanned codes: 1D barcodes from LCD and LED/OLED screens

Confirmation of scanning: light and sound signal

Degree of protection: IP54

Barcode scanner with stand, wired reader, automatic reading, RS232 interface HD10C

Model	HD10C-RS232	Light source	620nm LED
Scanning engine	CCD	Scanning method	automatically (after approaching the code), manually (push button)
Confirmation of scanning	light and sound signal	Scanning speed	200 times/second
Interface	RS232	Cable length	140 cm
Protection class	IP54	Dimensions of the device	16 x 9,5 x 6,5 cm
Dimensions of the base	24 x 12 x 12 cm	Package dimensions	18,5 x 12 x 8,5 cm
Device Weight	300 g	Weight with packaging	370 g
Operating temperature	-20 - 50°C	Storage temperature	-40 - 60°C
Readable 1D codes	CHINESE 2 of 5, CODABAR, CODE 11, CODE 128, CODE 39, CODE 93, EAN-13, EAN-8, Interleaved 2 of 5 (ITF), MSI, other one-dimensions, UPC-A, UPC-E		

